

TECHNICAL DATA SHEET EASY MIX WATER PLUG



DESCRIPTION

Easy Mix Water Plug is a rapid setting, cement based, impermeable mortar used for water leaks and seepage in concrete and masonry substrates.

Easy Mix Water Plug will set within 3 - 5 minutes (at normal temperatures), ready for the subsequent application of a suitable waterproofing membrane.

Easy Mix Water Plug is suitable as a plugging mortar for internal or external applications including:

- Rapid sealing of fast flowing water leaks and water seepage in concrete, concrete block walls, brickwork and all types of stone and masonry surfaces
- Emergency repairs on water pipes (including when under pressure)
- Emergency plugging of gas leaks
- Anchoring bolts and other accessories that require immediate use
- Underground basements, tunnels and sewers - to stop water under pressure

PRODUCT PACKAGING

Easy Mix Water Plug is available in 1kg buckets.

PRODUCT VOLUME

1kg of Easy Mix Water Plug fills approximately 600 – 650mls, depending on the mixing water used. The cavity volume is approximately 1.6kg/ litre.

SURFACE PREPARATION

- 1 For quickly sealing cracks and joints, chisel out the affected area to at least 3cm deep and approximately 4cm wide. Ensure that a square shape cut is made, and widen the wedge on the inside of the cut (as per diagram below). Avoid creating a 'V' shape.
- 2 Clean the surface to be waterproofed until it is free of concrete curing compounds, form release agents, paints and all other coatings, dirt and contamination.
- 3 It is important to wet the surface if water is not present at the time of application.

MIXING INSTRUCTIONS

Note: Shake bucket prior to mixing.

- 1 Mix only enough Easy Mix Water Plug which can be applied in three minutes and if it is a water leak, mix only the amount of material that can be used with your hand.
- 2 Fill a plastic or rubber container with Easy Mix Water Plug powder and slowly add water until a mortar like consistency is formed.
- 3 One kilogram of Easy Mix Water Plug requires approximately 250 - 280ml of water depending on weather conditions.

APPLICATION INSTRUCTIONS

As Easy Mix Water Plug is an alkaline material, ensure you wear gloves prior to application. Apply Easy Mix Water Plug with a trowel, a spatula or for best results, by hand. Do not pour the material in place.

LEAKS IN CRACKS OR JOINTS

- 1 Once the surface has been prepared, apply Easy Mix Water Plug in small amounts and mix only enough material that can be applied by hand. Knead the mixture with a gloved hand for approximately 15 seconds until the temperature of the mix increases and it becomes warm and slightly stiff.
- 2 Due to the rapid setting time of the mortar, application must be done quickly.
- 3 Mould the mortar into a cone like shape ready to fill the prepared area. Install the plugging mortar immediately and maintain firm hand pressure on it for about 30 seconds until it has set.
- 4 For large repairs, work from the lowest end of the repair towards the highest end, applying each new plugging mix next to the previous.
- 5 Immediately remove the excess material and continue until the crack is completely filled. When the area to be repaired is exposed to high fluid pressure, or in a tunnel or basement, do not try to plug up the crack all at once. Construct the repair in layers, allowing each to harden slightly before applying the next layer.

CURING

During normal weather conditions (18 - 20°C temperature range), Easy Mix Water Plug takes between three to five minutes to set.

When temperatures are hotter, use cold water or ice in the mixing water to delay the setting time.

CLEAN UP

Clean tools immediately with water. If the material has hardened, it will need to be removed via mechanical methods.

Note: Once the product has hardened and cured it should be sanded back and an approved waterproofing membrane applied over the top.

PRODUCT STORAGE

Easy Mix Water Stop Plug will keep for up to 6 months if kept sealed in its original container. High temperature and humidity after opening may reduce the storage life of the product.

PRECAUTIONS FOR USE

Easy Mix Water Plug contains cement powders which can be harmful to the skin.

During use, avoid inhalation of dust and contact with the skin and eyes. Wear suitable clothing, gloves, eye protection and respiratory protective equipment.

If contact with the skin occurs, thoroughly clean the area with plenty of fresh water and soap. In case of contact with the eyes, rinse with plenty of fresh water and seek medical advice.

If swallowed, seek medical attention immediately. Do not induce vomiting.

For further information consult the Material Safety Data Sheet and read the product label carefully before use.

Material Safety Data Sheets are available at www.easymixsales.com.au or by phoning 1800 077 744.

PLEASE NOTE

The information given in this data sheet is based on our current knowledge of the product when properly stored, handled and applied. We cannot guarantee that the product will be suitable, effective or safe when used for any purpose other than its stated uses.

To the extent that it is lawful, we exclude warranties implied by law and limit our liability to the cost of replacing the product. We accept no responsibility for loss or injury caused by improper use, incompetent preparation, inexpert or negligent application, or ordinary wear and tear.

Service or advice given by our staff should not amount to responsibility for the project - since the owner, or their contractor (and not River Sands), is responsible for procedures relating to the application of the product.



A Division of River Sands Pty Ltd
Cnr Riverland & Monte Khoury Dr
Loganholme Qld 4129, Australia

(07) 3412 8111 or 1800 077 744
www.easymixsales.com.au